

## ECOSTAT®- DF POLYCAN WL 2

- Application without conductive layer
- **Water based, 2 component epoxy paint**
- Glossy surface
- Colour grey ~ RAL 7035, other colours available on request
- Medium abrasion resistance
- Suitable for hard floors in EPA's
- Suitable for new and existing floors
- Easy application and rework using a roller
- Set includes a grounding connector
- Consumption: app. 1 kg for 2,5 m<sup>2</sup> (2 applications)

Typical resistance to ground  $R_G = 10^5 - 10^7$  ohm



Part Nr.	Pail
1131.7035.WL2.10	10 kg



User's instructions

## ECOSTAT®- DF POLYCAN MATT FINISH

- Application without conductive layer
- **Solvent based, 2 component polyurethane paint**
- Matt finish
- Colour grey, ~ RAL 7035, other colours available on request
- Medium abrasion resistance
- For horizontal and vertical surfaces
- Suitable for hard and resilient surfaces in EPA's
- Suitable for new and existing floors
- Easy application and rework using a roller
- Set includes a grounding connector
- Consumption: app. 1 kg for 4 m<sup>2</sup> (2 applications)

Typical resistance to ground  $R_G = 10^5 - 10^7$  ohm



User's instructions

Part Nr.	Pail
1132.7035.M.10	10 kg



**EASY application using a roller**

